

Radio parameters		RipEX	RipEX2
Frequency bands	135–154; 154–174; 215-240; 300–320; 320–340; 340–360; 368–400; 400–432; 432–470; 470-512; 928–960 MHz		135-175; 335-400; 400-470 MHz
Channel spacing	6.25 / 12.5 / 25 / 50 kHz		6.25 / 12.5 / 25 / 50 / 100 / 150 / 200 kHz
Frequency stability	+/- 1.0 ppm		
Modulation	QAM (Linear): 16DEQAM, D8PSK, π /4DQPSK, DPSK FSK (Exponential): 4CPFSK, 2CPFSK		QAM (Linear): 256QAM, 64QAM, 16DEQAM, D8PSK, π /4DQPSK, DPSK FSK (Exponential): 4CPFSK, 2CPFSK
FEC (Forward Error Correction)	On/Off, 3/4		On/Off, 2/3, 3/4, 5/6
Gross data rate	up to 167 kbps		up to 1.1 Mbps
RF Output power	0.1 to 10 W programmable		
Duty cycle	Continuous		
Rx to Tx Time	< 1.5 ms		
Sensitivity	- 99 dBm / 16DEQAM / 25 kHz -115 dBm / 2CPFSK / 25 kHz		- 93 dBm / 256QAM / 25 kHz -115 dBm / 2CPFSK / 25 kHz
Electrical			
Primary power	10 to 30 VDC, negative GND		
Rx	5 W/13.8 V; 4.8 W/24 V; (Radio part < 2 W)		8 W
Tx (dependent on RF power and modulation)	13 – 40 W		13 – 55 W
Sleep mode	0.1 W		0.01 W
Save mode	2 W		5 W
Interfaces			
Ethernet	1x 10/100 Base-T Auto MDI/MDIX / RJ45		4x 10/100/1000 Base-T Auto MDI/MDIX / RJ45
SFP	No		1×10/100/1000 Base-T/1000Base-SX/1000Base-LX
COM 1	RS232 / DB9F 300 – 115 200 bps		RS232/RS485 / DB9F 300 bps – 1 Mbps
COM 2	RS232/RS485 SW configurable / DB9F 300 – 115 200 bps		mPCIe expansion board 2x RS232
USB	USB 1.1 / Host A		USB 3.0 / Host A
Antenna	1x TNC female / 50 ohms (Rx/Tx) or 2x TNC (Rx+Tx) - different HW model		2x TNC female / 50 ohms SW configurable: 1x Rx/Tx or 1x Rx + 1x Tx
Inputs/Outputs	1x HW alarm input, 1x HW alarm output, 1x Sleep input		1x HW alarm input, 1x HW alarm output, 1x Sleep input, plus 2x DI, 2x DO, 1x difDI (when mPCIe-COMS is not used)
Indication LEDs			
LED panel	Power, ETH, COM1, COM2, Rx, Tx, Status		SYS, AUX, RX, TX, COM
ETH	No		4x RJ45 - 2x LED, 1x SFP - 1x LED
Environmental			
IP Code (Ingress Protection)	IP40, IP51		
MTBF (Mean Time Between Failure)	> 900.000 hours (> 100 years)		
Operating temperature	- 40 to +70 °C (- 40 to +158 °F)		
Operating humidity	5 to 95% non-condensing		
Mechanical			
Casing	Rugged die-cast aluminium		
Dimensions	50 H x 150 W x 118 D mm (1.97 x 5.9 x 4.65 in)		60 H x 185 W x 125 D x mm (2.34 x 7.2 x 4.9 in)
Weight	1.1 kg (2.4 lbs)		1.55 kg (3.4 lbs)
Mounting	DIN rail, L-bracket, Flat-bracket, 19" Rack shelf		
SW			
Operating modes	Bridge / Router		Bridge / Router (+Switch)
User protocols on COM	Modbus, IEC101, DNP3, PR2000, Comli, DF1, Profibus, Async Link, C24, Cactus, RP570, Slip, Siemens 3964(R)...		
User protocols on Ethernet	Modbus TCP, IEC104, DNP3 TCP, Comli TCP...		
Serial to IP convertors	Modbus RTU / Modbus TCP, DNP3 / DNP3 TCP, Terminal server		
Radio protocols	Transparent, Flexible, Base driven		
Multi master applications	Yes		
Report by exception	Yes		
Collision Avoidance Capability	Yes		
Remote to Remote communication	Yes		
Repeaters	Store-and-forward; Every unit; Unlimited number		
Optimization	Payload data and Ethernet / IP / TCP / UDP header compression, Packet flow on Radio channel optimization		
NTP (Network Time Protocol)	Client, Server (synchronized from internal GPS)		
Security			
Management	HTTP, HTTPS (own certificate), SSH		
Access accounts	2 levels (Guest, Admin)		4 levels (Guest, Tech, SecTech, Admin) x 3 users
Encryption	AES256		
IPsec	Yes		
RADIUS	No		Yes
Firewall	Layer 2 - MAC, Layer 3 - IP, Layer 4 - TCP/UDP		
HW tamper proof	No		Yes
Diagnostics and Management			
Radio link testing	Yes (ping with RSS, Data Quality, Homogeneity)		
Watched values	Device – Ucc, Temp, PWR, VSWR, HW Alarm Input Radio channel – RSScom, DQcom, TXLost [%] User interfaces – ETH [Rx/Tx], COM1 [Rx/Tx], COM2 [Rx/Tx]		
Statistics	For Rx/Tx Packets on User interfaces (ETH, COM1, COM2) User data and Radio protocol (Repeats, Lost, ACK etc.) on Radio channel		
Graphs	For Watched values and Statistics		
History (Statistics, Neighbours, Graphs)	20 periods (configurable, e.g. days)		
SNMP	SNMPv1, SNMPv2c, SNMPv3, SNMP Traps for Watched values		
Approvals	CE (RED), FCC, ATEX, RoHS		CE (RED), RoHS

RipEX – Radio modems



RipEX2

- 1.1 Mbps / 200 kHz / 256QAM
- 4× ETH, 1× SFP, 1× COM, 1× USB,
- RipEX compatible
- All RipEX features plus:
 - 6.25 - 200 kHz channel size
 - ACM, Adaptive FEC
 - RADIUS
 - HW tamper proof
 - Expansion ready - mPCIe
 - Full-duplex ready

RipEX is a **radio modem platform** renowned for overall data throughput in any real-time environment. RipEX radio modems are native IP devices, Software Defined with Linux OS that have been designed with attention to detail, performance and quality. All relevant state-of-the-art concepts have been carefully implemented.

RipEX, **1st generation**, is a best-in-class **compact radio modem** proven within the market since 2011 and used in thousands of installations.

RipEX2, **2nd generation**, was introduced in 2018. This **more powerful standard radio modem** provides significant improvements, especially in terms of data speed, security and number of interfaces.

RipEX-HS, a **fully redundant** 19" hot-standby **master station** with two radios and two power supplies and available for both, RipEX and RipEX2, is the final member of the RipEX family.

All RipEX devices provide a **24/7 reliable service for mission-critical applications** like SCADA & Telemetry for Electric and Water Utilities, Oil & Gas distribution and many other applications.




RipEX

- 166 kbps / 50 kHz / 16DEQAM
- 1× ETH, 2× COM, 1× USB
- Solar ready
- 0.1 – 10 watts
- - 40 to +70 °C
- WiFi management
- Customized protocols
- Backup routes
- Fast remote access
- IPsec



General overview



	RipEX	RipEX2
Max. Gross data rate	166 kbps	1.1 Mbps
Gross data rate / 25 kHz	83 kbps	167 kbps
Interfaces	1xETH, 2xCOM, 1xUSB	4xETH, 1xSFP, 1xCOM, 1xUSB
IPsec	Yes	Yes
RADIUS	No	Yes
Modulations	CPFSK - 16DEQAM	CPFSK - 256QAM
Channel size	6.25 - 50 kHz	6.25 - 200 kHz
Stream mode	Yes	No

Native IP device

Bridge mode – uses a **Transparent protocol** on the Radio channel, i.e. packets received on any interface are broadcast to the respective interfaces on all units in the network. Packets received on COM are broadcast to all COM's at all remote sites, allowing you to connect more RTU's to each remote unit.

Router mode – RipEX works as a standard IP Router with all interfaces (Radio and 1-5 Ethernet) and all COM ports without any compromise. Each of the five Ethernet ports on RipEX2 can be configured either as a switch or a router. There is an option of two protocols on the Radio channel: **Flexible** – unlimited anti-collision meshing without base stations or **Base driven** where all packet transmissions are managed by the local base station.

- **Switch** – switched or routed Ethernet ports (RipEX2)
- **Terminal server** - Serial-Ethernet converters, 5 independent sessions
- **TCP proxy** - converts TCP to UDP, eliminates transfer of TCP overhead
- **ARP proxy** - any IP address simulating (for RTU's without routing capabilities within the same subnet)
- **Subnets** - unlimited number of virtual Ethernet interfaces (IP aliases)
- **Shaping** - traffic management between Ethernet and Radio interface
- **IPsec, GRE, Firewall, DHCP, VLAN, NAPT, QoS...**

Data speed & Throughput

- **Possible Network throughput is achieved** by
 - **Min. Rx/Tx switching** and synchronization times
 - Optimum **Radio protocol** for the application
 - **Optimization**
 - payload data and headers compression
 - packet flow optimization on Radio channel
- Different data speeds for individual links
- **Auto-speed** - receiver is automatically adjusted to the data rate of the incoming frame
- **ACM** and **Adaptive FEC** (RipEX2)
- **Stream mode** - transmitting starts immediately on the Radio channel, without waiting for the end of the received frame on COM => zero latency

Channel size	Gross data rate		Possible Network throughput	
	RipEX	RipEX2	RipEX	RipEX2
6.25 kHz	21 kbps	42 kbps	> 25 kbps	> 50 kbps
12.5 kHz	42 kbps	83 kbps	> 50 kbps	> 100 kbps
25 kHz	83 kbps	167 kbps	> 100 kbps	> 200 kbps
50 kHz	167 kbps	333 kbps	> 200 kbps	> 400 kbps
100 kHz	–	555 kbps		> 700 kbps
150 kHz	–	925 kbps		> 1.1 Mbps
200 kHz	–	1.1 Mbps		> 1.4 Mbps

Security & Integrity

- **Licensed radio bands**
- **FEC**, interleaving, proprietary data compression
- **CRC32** data integrity control on Radio channel
- **Proprietary protocol** on Radio channel
- **Backup routes**
- **Digitally signed FW** (RipEX2)
- **Management** - https, ssh,
- **Role-based access control**
- **AES256** encryption
- **IPsec** - encrypted end-to-end tunnel
- **Firewall** - Layer 2 – MAC, Layer 3 – IP, Layer 4 – TCP/UDP

Radio protocols

- **Transparent / Bridge**
 - Repeater(s) supported
 - No collision avoidance capability
- **Flexible / Router**
 - Unlimited Tree topology
 - Multi-polling and report-by-exception concurrently
 - Nomadic mode - automatic routing
- **Base driven / Router**
 - Star topology, repeaters supported
 - Optimized for TCP/IP (IEC104)
 - Fair distribution of channel capacity among all remotes

Long range

- One radio hop over **50 km**
- **Line of sight not required**
- Carrier output power **0.1 - 10W**
- Exceptional data **sensitivity**
- **Any unit** can work **simultaneously as a repeater**
- **Unlimited** number of repeaters on the way
- Any IP network can interconnect RipEX units

Easy to configure and maintain

- **Web interface** or CLI via SSH
- **Wizards** - fast and simple setup
- **Non-intrusive management** via USB using either ETH/USB adapter or **WiFi**/USB adapter with DHCP
- **Fast remote access** - only the effective data are transferred over the air, html page downloaded from the local unit
- **External flash disc** - automatic configuration, SW keys and FW upgrade

Scalability

- **SW feature keys**
 - Advance features only when and where needed
 - Router, Speed, COM2 (SFP), 10W, Backup routes, (Duplex), Master
 - **Free Master-key trial** - for 30 days in every RipEX
- **HW models**
 - The same HW for Base, Repeater or Remote stations
 - Internal GPS module - NTP synchronization
 - mPCIe slot for expansion boards (RipEX2) GPS, 4G/3G/2G, 2x RS232...

Backup routes

- **Tested alternative paths** between two RipEX units
- **Automatic switch-over** to backup gateway, if primary route fails due to packet loss or weak RSS
- Backup gateway can be behind Radio or Eth interfaces
- **Unlimited number** of Alternative paths
- **Alternative path priority** assignment

RipEX-HS

- **Fully redundant hot-standby master station**
- Fully monitored
- **Automatic switchover** capability on detection of failure
- **Auto toggle** mode periodically switches units regardless of failure
- Two booted-up standard RipEX units inside
- **Switch-over** time < 2 s
- **Two independent power supplies**
- One or two antenna connectors
- **Hot swappable**
- 19" rack 3U

Reliability

- Units **tested in a climatic chamber** and in real traffic
- **Heavy-duty industrial components**
- Industrial rugged die-cast aluminium case
- IP40 or IP51
- **-40 to +70 °C**
- 3 year warranty

Diagnostics & Network Management

- **Statistic** logs for interfaces and communication links
- Historical and on-line values displayed in **graphs**
- 20 periods (e.g. days) of **history**
- **Watched values** (RSS, Ucc, Temp, PWR, etc.) also from neighbouring units
- **SNMP v3** including **Traps** and **Informs**
- HW **Alarm input**, HW **Alarm output**
- **Monitoring** – Real time/Save-to-file analysis of communication over any of the interfaces

SCADA protocols

- **Modbus, IEC101, DNP3, PR2000, Comli, DF1, Profibus, Async Link, C24, Cactus, RP570, Slip, Siemens 3964(R), IEC104, DNP3/TCP, Modbus TCP and others**
- SCADA serial protocol addresses are mapped to RipEX addresses
- TCP(UDP) protocols can be handled transparently or using Terminal server or TCP proxy
- Embedded **Modbus RTU / Modbus TCP converter**
- Each packet is transferred as an acknowledged unicast

Energy savings

- **Solar ready**
- **Sleep mode** - wake up triggered by Sleep digital input or by internal RTC (RipEX2)
- **Save mode** - wake up by a received packet from Radio channel or by Sleep digital input

