

	Husky IVO 150D	Husky IVO 350T	Husky IVO 350R	Husky IVO 700R	Husky IVO 1000R	Husky IVO 1800R
<b>Video performance</b> (based on video stream 1080p, 30fps, 5-8 Mbit/s/channel, recording with VMD enabled)						
<b>Throughput (up to)</b>	150 Mbit/s	360 Mbit/s	360 Mbit/s	720 Mbit/s	1080 Mbit/s	1800 Mbit/s
<b>Channel count (up to)</b>	20	50	50	100	150	250
<b>Local storage (max)</b>	16 TB	32 TB	32 TB	64 TB	128 TB	384 TB
<b>Hardware information</b>						
<b>Form factor</b>	Desktop Small Form Factor (SFF)	Desktop Tower Form Factor	Rack Mounted 1U	Rack Mounted 1U	Rack Mounted 2U	Rack Mounted 2U
<b>Dimensions (without bezel for rack units)</b>	290 x 92.6 x 292 (mm) 11.42" x 3.7 x 11.50"	335 x 177 x 345 (mm) 13.19" x 6.95" x 13.58"	42.8 x 482.0 x 577.6 (mm) 1.68" x 18.98" x 22.74"	42.8 x 434.0 x 534.5 (mm) 1.68" x 17.08" x 21.04"	86.8 x 434.0 x 693.81 (mm) 3.41" x 17.08" x 27.31"	86.8 x 448.0 x 810.0 (mm) 3.4" x 17.6" x 31.9"
<b>Weight</b>	5.26 kg (min) 11.57 lb (min)	9.358 kg (min) 20.63 lb (min)	8.74 kg (min) 19.27 lb (min)	13.6 kg 29.98 lb	29.68 kg 65.43 lb	40.0 kg 88.2 lb
<b>CPU</b>	Intel® Pentium® Gold G5400	Intel® Core™ i3-10100	Intel® Core™ i3-9100	Intel® Xeon® E-2236	Intel® Xeon® Silver 4210R	Intel® Xeon® Silver 4216
<b>GPU</b>	Integrated Intel® UHD Graphics 610 (Intel® Quick Sync Video)	Integrated Intel® UHD Graphics 630 (Intel® Quick Sync Video)	Integrated Intel® UHD Graphics 630 (Intel® Quick Sync Video)	No	No	No
<b>RAM</b>	8GB DDR4	16GB DDR4	16GB DDR4	16GB DDR4	16GB DDR4	32GB DDR4
<b>Operating system (OS)</b>	Windows 10 IoT Enterprise SAC	Windows 10 IoT Enterprise SAC	Windows 10 IoT Enterprise SAC	Windows 10 IoT Enterprise SAC	Windows Server 2019 IoT Essentials (No CAL) SAC	Windows Server 2019 IoT Essentials (No CAL) SAC
<b>VMS/OS storage</b>	256GB (M.2 PCIe NVMe)	1 x 256GB (M.2 PCIe NVMe)	1 x 256GB (M.2 PCIe NVMe)	2 x 240GB (RAID 1), M.2 SSDs on BOSS card	2 x 240GB (RAID 1), M.2 SSDs on BOSS card	2 x 240GB (RAID 1), M.2 SSDs on BOSS card
<b>Number of hard-drives</b>	1 x 3.5" (internal)	2 x 3.5" (internal)	2 x 3.5" (external accessible)	4 x 3.5" (hot-plug)	8 x 3.5" (prepared up to 12 x 3.5"), hot-plug	12 x 3.5" / 24 x 3.5" (hot-plug)
<b>Raw storage capacity (gross)</b>	2/4/8/12/16 TB (Dell enterprise grade drives)	4/8/16/24/32 TB (Dell enterprise grade drives)	4/8/16/24/32 TB (Dell enterprise grade drives)	8/16/32/48/64 TB (Dell enterprise grade drives)	16/32/64/96/128 TB (Dell enterprise grade drives)	24/48/96/144/192/288/384 TB (Dell enterprise grade drives)
<b>RAID support</b>	No	Intel® Rapid Storage Controller RAID 0,1 (Software RAID)	Intel® Rapid Storage Controller RAID 0,1 (Software RAID)	PERC H730P – RAID 0,1,5,6,10,50,60 RAID 5,6,10 configurable in Husky Assistant	PERC H730P – RAID 0,1,5,6,10,50,60 RAID 5,6,10 configurable in Husky Assistant	PERC H730P – RAID 0,1,5,6,10,50,60 RAID 5,6,10 configurable in Husky Assistant
<b>Display ports</b>	2 x DisplayPort™ 1 x VGA	2 x DisplayPort™ 1 x VGA	2 x USB 3.1 Type C / iGFX Display Port  USB-C to VGA Video Adapter included	1 x VGA	2 x VGA (1 Front & 1 Rear)	1 x VGA

	Husky IVO 150D	Husky IVO 350T	Husky IVO 350R	Husky IVO 700R	Husky IVO 1000R	Husky IVO 1800R
<b>Hardware information</b>						
<b>Network interface</b>	2 x 1 GbE (RJ45)	2 x 1 GbE (RJ45)	2 x 1 GbE (RJ45)	2 x 1 GbE (RJ45)	4 x 1 GbE (RJ45)	2 x 1 GbE + 2 x 10 GbE (RJ45)
<b>Available PCIe slots</b>	One Half Height PCIe x16 Gen 3	One PCI Express® x16 Gen 3 slot full height One PCI Express® x4 Gen 3 slot full height One PCI Express® x1 Gen 3 slot full height"	One PCI Express® x16 Gen 3 double width slot full height One PCI Express® x8 Gen 3 slot full height One PCI Express® x4 Gen 3 slot full height	One PCI Express® x16 Gen 3 slot full height / half length card with x8 bandwidth	One PCI Express® x16 Gen 3 slot full height / half length card	One PCI Express® x16 Gen 3 slot full height / half length card
<b>Archiving to external NAS</b>	Yes, through LAN port	Yes, through LAN port	Yes, through LAN port	Yes, through LAN port	Yes, through LAN port	Yes, through LAN port
<b>Archiving to external SAN</b>	No	No	No	No	No	Yes, through high-speed LAN card
<b>Credential and Key encryption</b>	Trusted Platform Module (TPM) 2.0	Trusted Platform Module (TPM) 2.0	Trusted Platform Module (TPM) 2.0	Trusted Platform Module (TPM) 2.0	Trusted Platform Module (TPM) 2.0	Trusted Platform Module (TPM) 2.0
<b>Redundant Power Supply</b>	No	No	No	Yes, hot-plug	Yes, hot-plug	Yes, hot-plug
<b>Remote Management</b>	No	No	No	Yes, iDRAC9 Enterprise (license incl.)	Yes, iDRAC9 Enterprise (license incl.)	Yes, iDRAC9 Enterprise (license incl.)
<b>Power consumption</b>						
<b>Power input</b>	100–240V, 50/60 Hz	100–240V, 50/60 Hz	100–240V, 50/60 Hz	100–240V, 50/60 Hz	100–240V, 50/60 Hz	100–240V, 50/60 Hz
<b>Max. Power consumption</b>	300W	460W	550W	350W	750W	1100W
<b>BTU rating</b>	1,024 BTU/hr (max. theoretical)	1,570 BTU/hr (max. theoretical)	1,875 BTU/hr (max. theoretical)	924.3 BTU/hr	1535.1 BTU/hr	1635.4 BTU/hr

**Service & support**

All units come with a standard five years warranty, with onsite support Next Business Day. Milestone is the single point of contact for support of the XProtect VMS and Husky IVO appliances. Onsite intervention is dispatched following Milestone's support processes – hardware Service Tag information accuracy required. Subject to regional availability, dependent on Dell Technologies support network

**Video Management System (VMS) information**

Milestone Husky IVO appliances are preloaded with Milestone XProtect VMS, which means that they can be used with any XProtect VMS variants. The required VMS licenses are purchased separately. The units can also be used with XProtect Essential+ with up to 8 cameras for free.